

KLT-PC5693 V4.2**5MP OmniVision OV5693 Auto Focus USB 2.0 Camera Module**

KLT-PC5693 V4.2 is a 5MP Auto Focus USB camera module based on 1/4" OV5693 image sensor. It delivers high-speed, 2K resolution ultra sharp image. The camera has a dedicated, high-performance fixed focus function providing best-in-class image and video output. This camera module is ideal solution for drones, automotive, agriculture farming, medical equipment, and traffic monitoring.

Key Features

- 2592 x 1944 OmniVision OV5693 sensor
- High speed USB 2.0 Plug and Play
- MJPEG and YUV2 output format
- Low power consumption
- Compact size
- UVC compliant to Windows, Linux, OS with UVC driver
- USB OTG (On-The-Go) support

KLT-PC5693 V4.2**5MP OmniVision OV5693 Auto Focus USB 2.0 Camera Module**


Camera Module No.	KLT-PC5693 V4.2
Resolution	5MP
Image Sensor	OV5693
Sensor Type	1/4"
Pixel Size	1.4 μ m x 1.4 μ m
EFL	3.20 mm
F.NO	2.80
Pixel	2592 x 1944
View Angle	70.0°(DFOV) 58.6°(HFOV) 45.3°(VFOV)
Lens Dimensions	8.50 x 8.50 x 5.65 mm
Module Type	Auto Focus
Interface	USB 2.0
Output Format	MJPEG / YUV2
Auto Control	Saturation, Contrast, Acutance White Balance, Exposure
Audio	Yes
Input Voltage	DC 5V
Working Current	Max 500mA
PCB Size	70.00 x 8.50 mm
System Compatibility	Windows XP (SP2, SP3), Vista, 7, 8, 10, 11 Android, Mac OS, Linux or OS with UVC Driver Raspberry Pi by USB Port
Software for USB Camera	AMCAP, Webcam Viewer, V4L2 Controls Contacam, VLC Player, MotionEye OS iSpy, ZoneMider, Yawcam
Lens Type	650nm IR Cut
Operating Temperature	-30°C to +70°C
USB Cable	USB Cable

Wide Compatibility with Windows, Android, Mac OS, Linux, or Raspberry Pi




Windows® android Mac™ OS Linux Raspberry Pi

www.KaiLapTech.com sales@KaiLapTech.com Tel: (852) 6908 1256 Fax: (852) 3017 6778

KLT-PC5693 V4.2**5MP OmniVision OV5693 Auto Focus USB 2.0 Camera Module**

Top View



Side View



Bottom View




USB Cable

KLT-PC5693 V4.2**5MP OmniVision OV5693 Auto Focus USB 2.0 Camera Module**

FORMAT	RESOLUTION	FRAME RATE
		USB 2.0
MJPEG	640 x 480 (VGA)	30 FPS
	1280 x 720 (720P)	30 FPS
	1920 x 1080 (1080P)	30 FPS
	2592 x 1944 (5MP)	30 FPS
YUV2	640 x 480 (VGA)	30 FPS
	1280 x 720 (720P)	10 FPS
	1920 x 1080 (1080P)	5 FPS









Periodic table of Elements

GROUP 1 1,008 H Hydrogen (Gas) 2 4,002 He Helium (Noble Gas)

3 6,941 Li Lithium (Alkali Metal) 4 9,01 Be Beryllium (Alkaline Earth Metal)

11 22,99 Na Sodium (Alkali Metal) 12 24,31 Mg Magnesium (Alkaline Earth Metal)

13 26,98 Al Aluminium (Other Metal) 14 28,08 Si Silicon (Metalloid) 15 30,97 P Phosphorus (Non-metal) 16 32,07 S Sulphur (Non-metal) 17 35,45 Cl Chlorine (Halogens) 18 39,95 Ar Argon (Noble Gas)

19 39,09 K Potassium (Alkali Metal) 20 40,08 Ca Calcium (Alkaline Earth Metal) 21 44,95 Sc Scandium (Transition Metal) 22 47,87 Ti Titanium (Transition Metal) 23 50,94 V Vanadium (Transition Metal) 24 51,99 Cr Chromium (Transition Metal) 25 54,94 Mn Manganese (Transition Metal) 26 55,85 Fe Iron (Transition Metal) 27 58,93 Co Cobalt (Transition Metal) 28 58,69 Ni Nickel (Transition Metal) 29 63,55 Cu Copper (Transition Metal) 30 65,39 Zn Zinc (Transition Metal) 31 69,72 Ga Gallium (Other Metal) 32 72,61 Ge Germanium (Metalloid) 33 74,92 As Arsenic (Non-metal) 34 78,96 Se Selenium (Non-metal) 35 79,90 Br Bromine (Halogens) 36 83,80 Kr Krypton (Noble Gas)

37 85,47 Rb Rubidium (Alkali Metal) 38 87,62 Sr Strontium (Alkaline Earth Metal) 39 88,91 Y Yttrium (Transition Metal) 40 91,22 Zr Zirconium (Transition Metal) 41 92,91 Nb Niobium (Transition Metal) 42 95,94 Mo Molybdenum (Transition Metal) 43 97,90 Tc Technetium (Transition Metal) 44 101,1 Rh Rhodium (Transition Metal) 45 102,9 Ru Ruthenium (Transition Metal) 46 106,4 Pd Palladium (Transition Metal) 47 107,9 Ag Silver (Transition Metal) 48 112,4 Cd Cadmium (Transition Metal) 49 114,8 In Indium (Other Metal) 50 118,7 Sn Tin (Other Metal) 51 121,8 Sb Antimony (Metalloid) 52 127,6 Te Tellurium (Metalloid) 53 126,9 I Iodine (Halogens) 54 131,3 Xe Xenon (Noble Gas)

55 132,9 Cs Cesium (Alkali Metal) 56 137,3 Ba Barium (Alkaline Earth Metal) 57-71 Lanthanides 72 178,5 Hf Hafnium (Transition Metal) 73 180,9 Ta Tantalum (Transition Metal) 74 183,8 W Tungsten (Transition Metal) 75 186,2 Re Rhenium (Transition Metal) 76 190,2 Os Osmium (Transition Metal) 77 192,2 Ir Iridium (Transition Metal) 78 195,1 Pt Platinum (Transition Metal) 79 196,9 Au Gold (Transition Metal) 80 200,6 Hg Mercury (Transition Metal) 81 204,4 Tl Thallium (Other Metal) 82 207,2 Pb Lead (Other Metal) 83 208,9 Bi Bismuth (Metalloid) 84 209 Po Polonium (Metalloid) 85 210 At Astatine (Halogens) 86 222 Rn Radon (Noble Gas)


87 223 Fr Francium (Alkali Metal) 88 226 Ra Radium (Alkaline Earth Metal) 89-103 Actinides 104 261 Rf Rutherfordium (Transition Metal) 105 262 Db Dubnium (Transition Metal) 106 263 Sg Seaborgium (Transition Metal) 107 264 Bh Bohrium (Transition Metal) 108 265 Hs Hassium (Transition Metal) 109 268 Mt Meitnerium (Transition Metal) 110 281 Ds Darmstadtium (Transition Metal) 111 280 Rg Roentgenium (Transition Metal) 112 285 Cn Copernicium (Transition Metal) 113 284 Nh Nihonium (Other Metal) 114 289 Fl Flerovium (Other Metal) 115 288 Mc Moscovium (Metalloid) 116 292 Lv Livermorium (Metalloid) 117 294 Ts Tennessine (Halogens) 118 294 Og Oganesson (Noble Gas)

57 138,9 La Lanthanum (Lanthanide) 58 140,1 Ce Cerium (Lanthanide) 59 140,9 Pr Praseodymium (Lanthanide) 60 144,2 Nd Neodymium (Lanthanide) 61 145 Pm Promethium (Lanthanide) 62 150,4 Sm Samarium (Lanthanide) 63 151,9 Eu Europium (Lanthanide) 64 157,2 Gd Gadolinium (Lanthanide) 65 158,9 Tb Terbium (Lanthanide) 66 162,5 Dy Dysprosium (Lanthanide) 67 164,9 Ho Holmium (Lanthanide) 68 167,2 Er Erbium (Lanthanide) 69 168,9 Tm Thulium (Lanthanide) 70 173 Yb Ytterbium (Lanthanide) 71 174,9 Lu Lutetium (Lanthanide)


89 232 Ac Actinium (Actinide) 90 232 Th Thorium (Actinide) 91 232 Pa Protactinium (Actinide) 92 238 U Uranium (Actinide) 93 239 Np Neptunium (Actinide) 94 239 Pu Plutonium (Actinide) 95 243 Am Americium (Actinide) 96 247 Cm Curium (Actinide) 97 251 Bk Berkelium (Actinide) 98 254 Cf Californium (Actinide) 99 254 Es Einsteinium (Actinide) 100 254 Fm Fermium (Actinide) 101 257 Md Mendelevium (Actinide) 102 258 No Nobelium (Actinide) 103 260 Lr Lawrencium (Actinide)

Version	Information
V1.0	First Version
V2.0	Add MIC
V4.0	Update ISP
V4.2	Change VCM


PIN NO	SIGNAL
PIN1	USB 5V
02	D-
03	D+
04	GND
05	shedding GND



BOTTOM VIEW



SIDE VIEW



TOP VIEW

Parameters:


1、Sensor specification:


Image Sensor: OV5693
Pixel: 1.4um×1.4um
Lens Type: 1/4
Important Voltage Description: USB 5V
(External power supply);

2、Lens specification:

FOV: 70°(D);58.6°(H);45.3°(V)
F/NO.: 2.8
TV distortion: <1.0%
Focal length: 3.2mm
Composition: 4P+IR FILTER
IR Cut Coating: 650nm±10nm@50%

Kai Lap Technologies Group Ltd

Designed By	Kevin	Model Name:	KLT-PC5693 V4.2			
Checked By	Aouly Yan	Projection Type:	Unit:	Date:		
			mm	5/7/2024		
		Third Angle	Scale:	Sheet:	Version:	
			1:1	1 of 1	1/0	



OV5693 5-megapixel product brief



available in
a lead-free
package

High-Performance 5-Megapixel Image Sensor for Front-Facing Cameras in Flagship Smartphones and Tablets

The OV5693 is OmniVision's highest performance 1/4-inch, 5-megapixel image sensor, delivering DSC-quality imaging and low-light performance as well as full 1080p high-definition video recording at 30 frames per second (fps). Using OmniVision's proprietary 1.4-micron OmniBSI-2™ pixel architecture, the OV5693 provides best-in-class low-light performance and image quality in a slim camera module. This makes the OV5693 an ideal camera solution for slim flagship smartphones and tablets, providing exceptional 5-megapixel "selfie" images and high-quality 1080p video.

Leveraging OmniVision's second-generation industry-leading backside illumination pixel technology, the OV5693 offers full resolution 5-megapixel images at 30 fps, an integrated scaler, and 2x2 binning

functionality with re-sampling filter. The scaler enables electronic image stabilization, while maintaining full field-of-view in both 720p and 1080p HD video modes. The 2x2 binning functionality, which features a post-binning re-sampling filter, further increases the sensor's sensitivity, while minimizing spatial artifacts and removing image artifacts around edges to produce crisp, clean color images.

The sensor features a high-speed 2-lane MIPI interface running up to 900 Mbps per lane and fits into an industry standard module size of 8.5 x 8.5 mm with a z-height of 4.2 mm for an autofocus module.

Find out more at www.ovt.com.



OmniVision.


Applications

- Cellular and Mobile Phones
- Digital Still Cameras (DSC)
- Digital Video Camcorders (DVC)
- PC Multimedia
- 3D Cameras

Product Features

- automatic black level calibration (ABLC)
- programmable controls for frame rate, mirror and flip, cropping, windowing, and scaling
- image quality controls: lens correction and defective pixel canceling
- supports output formats: 10-bit RAW RGB (MIPI)
- supports horizontal and vertical subsampling
- supports images sizes: 5MP, EIS1080p, 1080p, 720p, VGA, QVGA
- fast mode switching
- supports 3D applications
- support 2x2 binning, full scalar
- standard serial SCCB interface
- up to 2-lane MIPI serial output interface
- embedded 512 bytes one-time programmable (OTP) memory for part identification, etc.
- two on-chip phase lock loop (PLL)
- programmable I/O drive capability
- built-in 1.2V regulator for core
- built-in temperature sensor
- supports alternate row HDR timing

OV5693




Ordering Information

- **OV05693-G06H-3A**
(color, chip probing, 180 μ m backgrinding, reconstructed 8" wafer with good die)
- **OV05693-G36H-3A**
(color, chip probing, 180 μ m backgrinding, reconstructed 12" wafer with good die)

Product Specifications

- **active array size:** 2592 x 1944
- **power supply:**
- core: 1.16 - 1.3V (1.2V typical)
- analog: 2.6 - 3.0V
- I/O: 1.7 - 3.0V
- **power requirements:**
- active: 239 mW
- XSHUTDN: 1 μ W
- **temperature range:**
- operating: -30°C to +70°C junction temperature
- stable image: 0°C to +50°C junction temperature
- **output formats:** 10-bit RGB RAW
- **lens size:** 1/4"
- **lens chief ray angle:** 29.7° non-linear
- **input clock frequency:** 6 - 27 MHz
- **max S/N ratio:** 37.1 dB
- **dynamic range:** 68.0 dB @ 8x gain
- **maximum image transfer rate:**
- 5MP: 30 fps
- EIS1080p: 30 fps
- 1080p: 30 fps
- **sensitivity:** 1000 mV/lux-sec
- **scan mode:** progressive
- **pixel size:** 1.4 μ m x 1.4 μ m
- **dark current:** 3.3 mV/sec @ 60°C junction temperature
- **image area:** 3673.6 μ m x 2738.4 μ m
- **dimensions:**
- COB: 5350 μ m x 4800 μ m
- RW: 5400 μ m x 4850 μ m

Functional Block Diagram



4275 Burton Drive
Santa Clara, CA 95054
USA

Tel: +1 408 567 3000
Fax: +1 408 567 3001
www.ovt.com

OmniVision reserves the right to make changes to their products or to discontinue any product or service without further notice. OmniVision, the OmniVision logo and OmniPixel are registered trademarks of OmniVision Technologies, Inc. OmniBSI-2 is a trademark of OmniVision Technologies, Inc. All other trademarks are the property of their respective owners.



OmniVision

Cameras Applications



Automotive Driver Pilot




Live Streaming



Video Conference



Eye Tracker Biometric Detection



Machine Vision



Agricultural Monitor



Night Vision Security



Drone and Sports Eagle Eyes



Interactive Pet Camera



Cameras Applications

your BEST camera module partner



IMAGING DEVICES



Camera Module Pinout Definition Reference Chart

OmniVision Sony Samsung On-Semi Aptina Himax GalaxyCore PixArt SmartSens Sensors	
Pin Signal	Description
DGND GND	ground for digital circuit
AGND	ground for analog circuit
PCLK DCK	DVP PCLK output
XCLR PWDN XSHUTDOWN STANDBY	power down active high with internal pull-down resistor
MCLK XVCLK XCLK INCK	system input clock
RESET RST	reset active low with internal pull-up resistor
NC NULL	no connect
SDA SIO_D SIOD	SCCB data
SCL SIO_C SIOC	SCCB input clock
VSYNCS XVS FSYNCS	DVP VSYNC output
HREF XHS	DVP HREF output
DOVDD	power for I/O circuit
AFVDD	power for VCM circuit
AVDD	power for analog circuit
DVDD	power for digital circuit
STROBE FSTROBE	strobe output
FSIN	synchronize the VSYNC signal from the other sensor
SID	SCCB last bit ID input
ILPWM	mechanical shutter output indicator
FREX	frame exposure / mechanical shutter
GPIO	general purpose inputs
SLASEL	I2C slave address select
AFEN	CEN chip enable active high on VCM driver IC
MIPI Interface	
MDN0 DN0 MD0N DATA_N DMO1N	MIPI 1st data lane negative output
MDP0 DP0 MD0P DATA_P DMO1P	MIPI 1st data lane positive output
MDN1 DN1 MD1N DATA2_N DMO2N	MIPI 2nd data lane negative output
MDP1 DP1 MD1P DATA2_P DMO2P	MIPI 2nd data lane positive output
MDN2 DN2 MD2N DATA3_N DMO3N	MIPI 3rd data lane negative output
MDP2 DP2 MD2P DATA3_P DMO3P	MIPI 3rd data lane positive output
MDN3 DN3 MD3N DATA4_N DMO4N	MIPI 4th data lane negative output
MDP3 DP3 MD3P DATA4_P DMO4P	MIPI 4th data lane positive output
MCN CLKN CLK_N DCKN	MIPI clock negative output
MCP CLKP MCP CLK_P DCKN	MIPI clock positive output
DVP Parallel Interface	
D0 DO0 Y0	DVP data output port 0
D1 DO1 Y1	DVP data output port 1
D2 DO2 Y2	DVP data output port 2
D3 DO3 Y3	DVP data output port 3
D4 DO4 Y4	DVP data output port 4
D5 DO5 Y5	DVP data output port 5
D6 DO6 Y6	DVP data output port 6
D7 DO7 Y7	DVP data output port 7
D8 DO8 Y8	DVP data output port 8
D9 DO9 Y9	DVP data output port 9
D10 DO10 Y10	DVP data output port 10
D11 DO11 Y11	DVP data output port 11

Camera Reliability Test

Reliability Inspection Item			Testing Method	Acceptance Criteria
Category		Item		
Environmental	Storage Temperature	High 60°C 96 Hours	Temperature Chamber	No Abnormal Situation
		Low -20°C 96 Hours	Temperature Chamber	No Abnormal Situation
	Operation Temperature	High 60°C 24 Hours	Temperature Chamber	No Abnormal Situation
		Low -20°C 24 Hours	Temperature Chamber	No Abnormal Situation
	Humidity	60°C 80% 24 Hours	Temperature Chamber	No Abnormal Situation
	Thermal Shock	High 60°C 0.5 Hours Low -20°C 0.5 Hours Cycling in 24 Hours	Temperature Chamber	No Abnormal Situation
Physical	Drop Test (Free Falling)	Without Package 60cm	10 Times on Wood Floor	Electrically Functional
		With Package 60cm	10 Times on Wood Floor	Electrically Functional
	Vibration Test	50Hz X-Axis 2mm 30min	Vibration Table	Electrically Functional
		50Hz Y-Axis 2mm 30min	Vibration Table	Electrically Functional
		50Hz Z-Axis 2mm 30min	Vibration Table	Electrically Functional
	Cable Tensile Strength Test	Loading Weight 4 kg 60 Seconds Cycling in 24 Hours	Tensile Testing Machine	Electrically Functional
Electrical	ESD Test	Contact Discharge 2 KV	ESD Testing Machine	Electrically Functional
		Air Discharge 4 KV	ESD Testing Machine	Electrically Functional
	Aging Test	On/Off 30 Seconds Cycling in 24 Hours	Power Switch	Electrically Functional
	USB Connector	On/Off 250 Times	Plug and Unplug	Electrically Functional



Inspection Item			Inspection Method	Standard of Inspection	
Category		Item			
Appearance	FPC/ PCB	Color	The Naked Eye	Major Difference is Not Allowed.	
		Be Torn/Chopped	The Naked Eye	Copper Crack Exposure is Not Allowed.	
		Marking	The Naked Eye	Clear, Recognizable (Within 30cm Distance)	
	Holder	Scratches	The Naked Eye	The Inside Crack Exposure is Not Allowed	
		Gap	The Naked Eye	Meet the Height Standard	
		Screw	The Naked Eye	Make Sure Screws Are Presented (If Any)	
		Damage	The Naked Eye	The Inside Crack Exposure is Not Allowed	
	Lens	Scratch	The Naked Eye	No Effect On Resolution Standard	
		Contamination	The Naked Eye	No Effect On Resolution Standard	
		Oil Film	The Naked Eye	No Effect On Resolution Standard	
		Cover Tape	The Naked Eye	No Issue On Appearance.	
	Function	Image	No Communication	Test Board	Not Allowed
			Bright Pixel	Black Board	Not Allowed In the Image Center
Dark Pixel			White board	Not Allowed In the Image Center	
Blurry			The Naked Eye	Not Allowed	
No Image			The Naked Eye	Not Allowed	
Vertical Line			The Naked Eye	Not Allowed	
Horizontal Line			The Naked Eye	Not Allowed	
Light Leakage			The Naked Eye	Not Allowed	
Blinking Image			The Naked Eye	Not Allowed	
Bruise			Inspection Jig	Not Allowed	
Resolution			Chart	Follows Outgoing Inspection Chart Standard	
Color			The Naked Eye	No Issue	
Noise			The Naked Eye	Not Allowed	
Corner Dark			The Naked Eye	Less Than 100px By 100px	
Color Resolution			The Naked Eye	No Issue	
Dimension			Height	The Naked Eye	Follows Approval Data Sheet
		Width	The Naked Eye	Follows Approval Data Sheet	
		Length	The Naked Eye	Follows Approval Data Sheet	
		Overall	The Naked Eye	Follows Approval Data Sheet	

KLT Package Solutions

KLT Camera Module



Complete with Lens Protection Film



Tray with Grid and Space



Place Cameras on the Tray



Camera Modules Package Solution

Full Tray of Cameras



Cover Tray with Lid



Put Tray into Anti-Static Bag



Vacuum the Anti-Static Bag



Camera Modules Package Solution

Sealed Vacuum Bag with Labels

1. Model and Description 2. Quantity 3. Shipping Date 4. Caution



Large Order Package Solution

Place Foam Sheets Between Trays



Foam Sheets are Slightly Larger than Trays



Place Foam Sheets and Trays into Box



Foam Sheets are Tightly Fitting Box



Small Order Package Solution

Place Foam Sheets and Trays into Small Box



Foam Sheets are Nicely Fitting the Small Box



Package in Small Box for Shipment



Place Small Boxes into Larger Box



Carbon Box Package Solution

Seal the Carbon Box

Final Package Labelled Box



Carbon Box Ready for Shipment

1. Delivery Address and Phone No. 2. Box No. and Ship Date 3. Fragile Caution



Sample Order Package Solution

Place Sample into Small Anti-Static Bag



Place Connectors into Small Ant-Static Bag



Sample Labels on the Small Bag

1. Camera Module or Connector Model 2. Shipping Date and Quantity 3. Caution



Connectors Large Order Package Solution

Connectors in a Wheel



Label Connectors in the Wheel



The Wheel is Perfectly Fitting the Box



Connectors Box Ready for Shipment





CMOS CAMERA MODULES




your BEST camera module partner

Company Kai Lap Technologies (KLT)

Kai Lap Technologies Group Limited. (KLT) was established in 2009, a next-generation technology driven manufacturer specialized in research, design, and produce of audio and video products. KLT is occupying 20,000 square feet automated plants with 100 employees of annual throughput 30,000,000 units cameras.

KLT provides OEM, ODM design, contract manufacturing, and builds the camera products. You may provide the requirements to us, even with a hand draft, our sales and engineering work together to meet your needs. We consider ourselves your last-term partner in developing practical and innovative solutions.

Our team covers everything from initial concept development to mass produced product. KLT specializes in customized camera design, raw material, electronic engineering, firmware/software development, product testing, and packing design. Our experienced strategic supply systems offer a robust and dependable manufacturing capacity for orders of various sizes.



Limited Warranty

KLT provides the following limited warranty if you purchased the Product(s) directly from KLT company or from KLT's website, www.KaiLapTech.com. Product(s) purchased from other sellers or sources are not covered by this Limited Warranty. KLT guarantees that the Product(s) will be free from defects in materials and workmanship under normal use for a period of one (1) year from the date you receive the product ("Warranty Period").

For all Product(s) that contain or develop material defects in materials or workmanship during the Warranty Period, KLT will, at its sole option, either: (i) repair the Product(s); (ii) replace the Product(s) with a new or refurbished Product(s) (replacement Product(s) being of identical model or functional equivalent); or (iii) provide you a refund of the price you paid for the Product(s).

This Limited Warranty of KLT is solely limited to repair and/or replacement on the terms set forth above. KLT is not reliable or responsible for any subsequent events.



www.KaiLapTech.com sales@KaiLapTech.com Tel: (852) 6908 1256 Fax: (852) 3017 6778



CMOS CAMERA MODULES



your BEST camera module partner

KLT Strength

Powerful Factory



Professional Service



Promised Delivery



www.KaiLapTech.com sales@KaiLapTech.com Tel: (852) 6908 1256 Fax: (852) 3017 6778

All rights reserved @ Kai Lap Technologies Group Ltd. Specifications subject to change without notice.